## Cromalent Green S12

## Chemical Nature: Mixture of Monoazo Copper and Chromium complex

## **Physical Properties**

Form	Powder	
Colour	Green	
Solubility in water	Insol.	
Specific gravity (water=1)	1.35	
Light Fastness		
1-8 Blue Scale comparison	5	
Heat Fastness		
10 min. 180°C (1-5 scale)	3	
Chemical Fastness		
Acid (1-5 scale)	5	
Alkali (1-5 scale)	5	
Table of solubilities		
Methanol	360	
Ethanol	200	
Isopropanol	300	
Isobutanol	260	
n-Butanol	280	
Ethylacetate	290	
Toluene	350	
Xylene	270	
MEK	500	
MIBK	280	
Ethyl Cellosolve	280	
Cyclo-Hexanone	260	
PM (Propylene Glycol Methyl Ether)	370	
DPM (Dipropylene Glycol Methyl Ether)	330	
Acetone	140	

APPLICATIONS		
Wood Stains	Α	
Hot stamping	Α	
Natural or sinthetic leather coatings	Α	
Soles of shoes coatings	Α	
Transparent coating for aluminium foil	А	
Transparent coating for metallized film	А	
Solvent based flexografic inks	Α	
Ink-jet inks	Α	

2,5%	RECIPE FOR ILLUSTRATION	1%
9	NC resine	9
21	Ethylacetate	21
10	Metoxipropanol	10
27,5	MEK	29
30	Ethanol	30
2,5	Dye	1
100		100

Legenda: A= suitable, B= applicable previous tests, C= unsuitable. Illustrations have been obtained by a 24 micron coater.

Fastness methods: Light: ISO blue scale (1-8) as comparison standard. / Heat: Automatic constant temperature dryer at 180°C for 10 minutes. / Acid: Immerse in 1% H2SO solution for 24 h. / Alkali: Immerse in 1% NaOH solution for 24h.

Solubilities: Figures given in the table represent the amount of dye in grams which may be dissolved in a litre of the indicated solvent. Test is conducted for each solvent by making a sequence of drawdowns with a 30 micron coater on aluminium foil at increasing values of solved dye. Drawdown must be glossy ans trasparent, with no opacity, while no bottom must be present in the container.

Other informations: The above informations are based on our actual knowledge and on the results of the tests in our lab, but they are given without guarantee. Tests before the industrial use of the product are recommended.